

LOW TEMPERATURE APPLICATIONS

Zodiaq® quartz surfaces are suitable for low temperature exposures including applications where the product is exposed to freeze-thaw cycling.

Materials that readily absorb moisture are especially prone to cracking from expansion and contraction when exposed to temperature swings between subfreezing and above-freezing conditions. Zodiaq® is a nonporous product and has low moisture absorption. As a result, Zodiaq® is less subject to cracking than more porous materials like natural stone, when exposed to freeze-thaw conditions. Zodiaq® performance is categorized as "Unaffected" (i.e., no damage) in accordance with ASTM C1026, Standard Test Method for Resistance of Ceramic Tile to Freeze-Thaw Cycling, making it suitable for cold food service applications as well as for outdoor storage. When storing Zodiaq® outdoors, special precautions must be taken to prevent damage; refer to slab storage bulletin.

The coefficient of thermal expansion for Zodiaq® is relatively small, 1.45×10^{-5} in/in/°C, however this value should be taken into account for design scenarios where expansion and contraction are anticipated to occur.

Q90-K03156-9 1/04

The information contained in this Technical Bulletin is given by E.I. du Pont de Nemours and Company free of charge. It is based on technical data which DuPont believes to be reliable and is intended for use by persons having knowledge of this technical area at their own discretion and risk. Seller assumes no responsibility for results obtained or damage incurred from the use of this Technical Bulletin either in whole or in part by a buyer of Zodiaq®. Zodiaq® is a DuPont registered trademark for its quartz surfaces. Only DuPont makes Zodiaq®. Copyright © 2004 E.I. du Pont de Nemours and Company. Printed in the U.S.A.

DuPont™
ZODIAQ®
QUARTZ SURFACES



The miracles of science