



PLAS-TEX® PolyWall

WHAT IS IT?

PolyWall is an extruded **PLAS-TEX®** sheet with an embossed Matte textured surface, similar to vinyl wall covering.

FEATURES

- 100% Waterproof
- Fiberglass free
- Does not support mold, mildew, or bacteria growth
- Chemically inert
- Color goes all the way through
- Attractive matte texture
- Made from 100% recycled resins
- USDA compliant/CFIA approved
- Easy installation

BENEFITS

- Non-absorbent: no swelling, rotting, or water discoloration
- No irritating, harmful fiberglass dust
- Hygienic: does not contribute to "sick"-building syndrome
- Not affected by acids, harsh chemical solvents or petroleum products
- For interior use
- Scratches don't show makes for extended product life
- High-performance sanitary sheet that blends with most décors
- Passes most interior building codes
- Contributes to Green Building: scrap can be recycled as grade #7
- Use in federally inspected food processing plants
- Can be scored with utility knife and snapped

TYPICAL APPLICATIONS

PolyWall can be used for both commercial and residential settings that have a lot of moisture or are washed down for cleanliness. Field applications include:

- Bathroom Walls
- Tub Kits for renovation of Hotel Rooms
- Tub Enclosure above Tub Kit
- Laundry Rooms
- Utility Rooms
- Commercial Restrooms
- Commercial Utility Rooms
- Commercial Kitchens
- Break Rooms
- Shelf Liners



In the home, apply in bathrooms, laundry and utility rooms, or use as shelf liner. Our sanitary sheet can be found on the walls of hotel tub wall surrounds, restaurant kitchens, laundromats, gyms, locker room showers, and commercial restrooms.

INSTALLATION INFORMATION

Install over an unfinished, smooth, sound wall with moisture-curing, non-flammable latex adhesive using a notched trowel. When installing over a non-porous surface, such as a painted wall or ceramic tile, our proprietary **Parkland Panel Adhesive** is strongly recommended. Precondition panels and moldings for 24 hours at the final temperature in the room to be applied. Allow 72 hours for adhesive to cure.

LOW MAINTENANCE

Maintenance is simple with a clean rag and any household cleaner. **PLAS-TEX®** is unaffected by most corrosive chemicals and solvents. Do not use abrasive cleansers.

PRODUCT RANGE

Sizes:

Thicknesses: 0.040" - 3/16"
Widths: up to 4'
Lengths: up to 10'
In Stock: 0.060" x 48" x 96",
0.060" x 48" x 120"

Accessories:

Matched PVC moldings - 0.090", 3/16" gap
Nylon rivets - 3/4" to 1 1/2"

Recommended Adhesives: trowel grade, non-flammable

Texture:

Matte

Parkland Panel Adhesive

Henry 444 FRP panel adhesive
Super-Tek PanelSet FRP
Liquid Nails FRP-310 latex FRP adhesive

Colors:

Bright White
Almond (Special Order)
Light Gray (Special Order)